



# Safety Data Sheet

according to WHS Regulations

Print date: 27.03.2023

Revision date: 27.03.2023

## 1 Identification

**Product Name:** 72-847A Trim Tex Adhesive**Other Means of Identification:** Mixture**Recommended Use of the Chemical and Restriction on Use:** Adhesive**Details of Manufacturer or Importer:**Wallboard Tool Co. Pty Ltd  
30 Leda Drive  
Burleigh, QLD 4220  
Australia**Phone Number:** 07 5535 7655 / 1300 653 177**Emergency telephone number:** National Poisons Information Centre: 13 11 26

## 2 Hazard(s) Identification

**Hazardous Nature:**

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition).



Flame

Aerosol 1                      H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



Health hazard

STOT RE 2                      H373                      May cause damage to organs through prolonged or repeated exposure.



Environment

Aquatic Chronic 2                      H411                      Toxic to aquatic life with long lasting effects.

Skin Corrosion/Irritation 2   H315                      Causes skin irritation.  
Eye Irritation 2A                      H319                      Causes serious eye irritation.  
Skin Sensitisation 1                      H317                      May cause an allergic skin reaction.  
STOT SE 3                      H336                      May cause drowsiness or dizziness.**Signal Word** Danger**Hazard Statements**H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.  
H315                      Causes skin irritation.  
H319                      Causes serious eye irritation.  
H317                      May cause an allergic skin reaction.  
H336                      May cause drowsiness or dizziness.  
H373                      May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

# Safety Data Sheet

according to WHS Regulations

Print date: 27.03.2023

Revision date: 27.03.2023

**Product Name: 72-847A Trim Tex Adhesive**

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

**Precautionary Statements**

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection / face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3 Composition and Information on Ingredients

**Chemical Characterization: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Hazardous Components:**

CAS: 67-64-1	Acetone	20-<50%
	⚠ Flammable Liquids 2, H225; ⚠ Eye Irritation 2A, H319; STOT SE 3, H336	
CAS: 74-98-6	Propane	10-<20%
	⚠ Flam. Gas 1A, H220; ⚠ Press. Gas L, H280	
CAS: 79-20-9	Acetic acid, methyl ester	5-<10%
	⚠ Flammable Liquids 2, H225; ⚠ Eye Irritation 2A, H319; STOT SE 3, H336	
CAS: 115-10-6	Dimethyl ether	5-<10%
	⚠ Flam. Gas 1A, H220; ⚠ Press. Gas C, H280	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	5-<10%
	⚠ STOT RE 1, H372; ⚠ Aspiration Hazard 1, H304; ⚠ Skin Corrosion/Irritation 2, H315; ⚠ Eye Irritation 2A, H319	
CAS: 98-56-6	1-Chloro-4-(trifluoromethyl)benzene	1-<5%
	⚠ Flammable Liquids 3, H226; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sensitisation 1, H317	
CAS: 142-82-5	Heptane	1-<5%
	⚠ Flammable Liquids 2, H225; ⚠ Aspiration Hazard 1, H304; ⚠ Aquatic Chronic 1, H410; ⚠ Skin Corrosion/Irritation 2, H315; STOT SE 3, H336	
CAS: 67-56-1	Methanol	0.1-<1%
	⚠ Flammable Liquids 2, H225; ⚠ Acute Toxicity (Oral) 3, H301; ⚠ Acute Toxicity (Dermal) 3, H311; ⚠ Acute Toxicity (Inhalation) 3, H331; ⚠ STOT SE 1, H370	

(Contd. on page 3)

# Safety Data Sheet

according to WHS Regulations

Print date: 27.03.2023

Revision date: 27.03.2023

**Product Name: 72-847A Trim Tex Adhesive**

(Contd. of page 2)

CAS: 108-87-2	Methylcyclohexane	0.1-<1%
	 Flammable Liquids 2, H225;  Aspiration Hazard 1, H304;  Aquatic Chronic 2, H411;  Skin Corrosion/Irritation 2, H315; STOT SE 3, H336	
CAS: 841251-34-1	Maleic Anhydride Modified Liquid Polyisoprene	0.1-<1%

## 4 First Aid Measures

**Inhalation:**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

**Skin Contact:**

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if irritation develops and persists.

**Eye Contact:**

In case of eye contact, rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Seek medical attention.

**Ingestion:**

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

**Symptoms Caused by Exposure:**

Inhalation: May cause respiratory irritation. May cause drowsiness or dizziness.

Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Eye Contact: Causes serious eye irritation.

Ingestion: May cause gastrointestinal irritation, nausea, diarrhoea and vomiting.

## 5 Fire Fighting Measures

**Suitable Extinguishing Media:**

Use fire extinguishing methods suitable to surrounding conditions. Do not use water jet.

**Specific Hazards Arising from the Chemical:**

Hazardous combustion products include oxides of carbon and various hydrocarbons.

Product is extremely flammable. Vapours may travel considerable distances to a source of ignition where they can ignite, flashback, or explode.

Pressurised container: may burst if heated. Containers close to fire should be removed if safe to do so. Use water spray to cool fire exposed containers.

Prevent run-off from fire fighting entering drains or water courses.

**Special Protective Equipment and Precautions for Fire Fighters:**

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

## 6 Accidental Release Measures

**Personal Precautions, Protective Equipment and Emergency Procedures:**

Wear approved respiratory protection, chemical resistant gloves, protective clothing and safety boots.

Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation.

Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

**Environmental Precautions:**

In the event of a major spill, prevent spillage from entering drains or water courses.

**Methods and Materials for Containment and Cleaning Up:**

Stop leak if safe to do so, sealing the leaking container. Collect the leaking containers and place in a well-ventilated area, preferable an operating exhaust hood. Collect as much spilled material as possible using only non-sparking tools.

(Contd. on page 4)

# Safety Data Sheet

according to WHS Regulations

Print date: 27.03.2023

Revision date: 27.03.2023

**Product Name: 72-847A Trim Tex Adhesive**

(Contd. of page 3)

## 7 Handling and Storage

**Precautions for Safe Handling:**

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours or mists. Use only outdoors or in a well-ventilated area.

Take precautionary measures against static discharge. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

**Conditions for Safe Storage:**

Store in a cool, dry and well ventilated area. Do not expose to temperatures exceeding 50 °C. Protect from heat, sparks, open flames and other sources of ignition.

## 8 Exposure Controls and Personal Protection

**Exposure Standards:****CAS: 67-64-1 Acetone**

WES	STEL: 2375 mg/m <sup>3</sup> , 1000 ppm TWA: 1185 mg/m <sup>3</sup> , 500 ppm
-----	--

**CAS: 74-98-6 Propane**

WES	Asphyxiant
-----	------------

**CAS: 79-20-9 Acetic acid, methyl ester**

WES	STEL: 757 mg/m <sup>3</sup> , 250 ppm TWA: 606 mg/m <sup>3</sup> , 200 ppm
-----	---

**CAS: 115-10-6 Dimethyl ether**

WES	STEL: 950 mg/m <sup>3</sup> , 500 ppm TWA: 760 mg/m <sup>3</sup> , 400 ppm
-----	---

**CAS: 142-82-5 Heptane**

WES	STEL: 2050 mg/m <sup>3</sup> , 500 ppm TWA: 1640 mg/m <sup>3</sup> , 400 ppm
-----	---

**CAS: 67-56-1 Methanol**

WES	STEL: 328 mg/m <sup>3</sup> , 250 ppm TWA: 262 mg/m <sup>3</sup> , 200 ppm Sk
-----	---

**CAS: 108-87-2 Methylcyclohexane**

WES	TWA: 1610 mg/m <sup>3</sup> , 400 ppm
-----	---------------------------------------

**Engineering Controls:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapour below occupational exposure standards. Use explosion-proof ventilating equipment.

**Respiratory Protection:**

Use an approved organic vapour (filter type A) respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapour, inadequate ventilation, development of respiratory tract irritation) and engineering controls are not feasible. See Australian Standards AS/NZS 1715 and 1716 for more information.

**Skin Protection:**

Chemical resistant gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information.

When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

(Contd. on page 5)

# Safety Data Sheet

according to WHS Regulations

Print date: 27.03.2023

Revision date: 27.03.2023

**Product Name: 72-847A Trim Tex Adhesive**

(Contd. of page 4)

**Eye and Face Protection:**

Safety glasses with top and side shields or goggles. See Australian/New Zealand Standards AS/NZS 1336 and 1337 for more information.

## 9 Physical and Chemical Properties

**Appearance:**

<b>Form:</b>	Aerosol
<b>Colour:</b>	No information available
<b>Odour:</b>	No information available
<b>Odour Threshold:</b>	No information available
<b>pH-Value:</b>	No information available
<b>Melting point/freezing point:</b>	No information available
<b>Initial Boiling Point/Boiling Range:</b>	No information available
<b>Flash Point:</b>	-104 °C (estimated)
<b>Flammability (solid, gas):</b>	No information available
<b>Auto-ignition Temperature:</b>	No information available
<b>Decomposition Temperature:</b>	No information available
<b>Explosion Limits:</b>	
<b>Lower:</b>	2.4 Vol %
<b>Upper:</b>	12.1 Vol %
<b>Vapour Pressure at 20 °C:</b>	4137 - 5516 hPa
<b>Density:</b>	1.047 g/cm <sup>3</sup> (estimated)
<b>Vapour Density:</b>	No information available
<b>Evaporation Rate:</b>	No information available
<b>Solubility in Water:</b>	No information available
<b>Partition Coefficient (n-octanol/water):</b>	No information available

## 10 Stability and Reactivity

**Possibility of Hazardous Reactions:** No dangerous reactions known under conditions of normal use.**Chemical Stability:** Stable at ambient temperature and under normal conditions of storage and use.**Conditions to Avoid:** Exposure to temperatures above 50 °C.**Incompatible Materials:** None known.**Hazardous Decomposition Products:** Oxides of carbon and various hydrocarbons.

## 11 Toxicological Information

**Toxicity:****LD50/LC50 Values:****CAS: 67-64-1 Acetone**

Oral	LD50	5,800 mg/kg (Rattus norvegicus (rat))
	LD50	>7,426 mg/kg (Oryctolagus cuniculus (rabbit))
Inhalation	LC50/4 h	30,000 ppm (Rattus norvegicus (rat))

**CAS: 74-98-6 Propane**

Inhalation	LC50/4 h	658 mg/l (Rattus norvegicus (rat))
------------	----------	------------------------------------

**CAS: 79-20-9 Acetic acid, methyl ester**

Oral	LD50	6,482 mg/kg (Rattus norvegicus (rat))
		3,705 mg/kg (Oryctolagus cuniculus (rabbit))

**CAS: 115-10-6 Dimethyl ether**

Inhalation	LC50/4 h	308 mg/l (Rattus norvegicus (rat))
------------	----------	------------------------------------

(Contd. on page 6)

# Safety Data Sheet

according to WHS Regulations

Print date: 27.03.2023

Revision date: 27.03.2023

**Product Name: 72-847A Trim Tex Adhesive**

(Contd. of page 5)

<b>CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light</b>		
Oral	LD50	4,820 mg/kg (Rattus norvegicus (rat))
	LD50	>1,900 mg/kg (Oryctolagus cuniculus (rabbit))
Inhalation	LC50/4 h	>4.96 mg/l (Rattus norvegicus (rat))
<b>CAS: 98-56-6 1-Chloro-4-(trifluoromethyl)benzene</b>		
Oral	LD50	382 mg/kg (Rattus norvegicus (rat))
	LD50	0.5-1 mg/kg (Rattus norvegicus (rat))
Inhalation	LC50/4 h	220 ppm (Rattus norvegicus (rat))
<b>CAS: 142-82-5 Heptane</b>		
Oral	LD50	>15,000 mg/kg (Rattus norvegicus (rat))
	LD50	>2,000 mg/kg (Oryctolagus cuniculus (rabbit))
Inhalation	L50/4 h	103,000 mg/m <sup>3</sup> (Rattus norvegicus (rat))
<b>CAS: 67-56-1 Methanol</b>		
Inhalation	LC50/4 h	83.8 mg/l (Rattus norvegicus (rat))
<b>CAS: 108-87-2 Methylcyclohexane</b>		
Oral	LD50	2,250 mg/kg (mus)
	LD50	>2,000 mg/kg (Oryctolagus cuniculus (rabbit))
Inhalation	LC50/4 h	16 mg/l (Rattus norvegicus (rat))

**Acute Health Effects****Inhalation:** May cause respiratory irritation. May cause drowsiness or dizziness.**Skin:** Causes skin irritation. May cause an allergic skin reaction.**Eye:** Causes serious eye irritation.**Ingestion:** May cause gastrointestinal irritation, nausea, diarrhoea and vomiting.**Skin Corrosion / Irritation:** Causes skin irritation.**Serious Eye Damage / Irritation:** Causes serious eye irritation.**Respiratory or Skin Sensitisation:** May cause an allergic skin reaction.**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:**

Based on classification principles, the classification criteria are not met.

1-Chloro-4-(trifluoromethyl)benzene is classified by IARC as Group 2B - Possibly carcinogenic to humans.

**Reproductive Toxicity:** Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:** May cause drowsiness and dizziness.**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:** Based on classification principles, the classification criteria are not met.**Chronic Health Effects:** No information available**Existing Conditions Aggravated by Exposure:** No information available**12 Ecological Information****Ecotoxicity:****Aquatic toxicity:**

Toxic to aquatic life with long lasting effects.

**CAS: 67-64-1 Acetone**

EC50/48 h | 12,600 mg/l (Daphnia magna (water flea))

(Contd. on page 7)

# Safety Data Sheet

according to WHS Regulations

Print date: 27.03.2023

Revision date: 27.03.2023

**Product Name: 72-847A Trim Tex Adhesive**

(Contd. of page 6)

LC50/96 h	4,740-6,330 mg/l (Oncorhynchus mykiss (rainbow trout))
<b>CAS: 79-20-9 Acetic acid, methyl ester</b>	
EC50/48 h	1,026.7 mg/l (Daphnia magna (water flea))
LC50/96 h	295-348 mg/l (Pimephales promelas (fathead minnow))
<b>CAS: 115-10-6 Dimethyl ether</b>	
EC50/48 h	4.3-7.8 mg/l (Daphnia magna (water flea))
LC50/96 h	10.302-16.743 mg/l (fish)
<b>CAS: 142-82-5 Heptane</b>	
EC50/24 h	>10 mg/l (Daphnia magna (water flea))
LC50/96 h	375 mg/l (fish)
<b>CAS: 67-56-1 Methanol</b>	
LC50/96 h	13,500-17,600 ppm (Lepomis macrochirus (bluegill))
	19,500-20,700 ppm (Oncorhynchus mykiss (rainbow trout))
LC50/96 h	28,200 mg/l (Pimephales promelas (fathead minnow))
<b>CAS: 108-87-2 Methylcyclohexane</b>	
LC50/96 h	5.8 mg/l (fish)

**Persistence and Degradability:** No data available on finished product.**Bioaccumulative Potential:** No data available on finished product.**Mobility in Soil:** No data available on finished product.**Other adverse effects:** No further relevant information available.

## 13 Disposal Considerations

**Disposal Methods and Containers:** Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

## 14 Transport Information

**UN Number****ADG, IMDG, IATA** UN1950**Proper Shipping Name****ADG, IMDG, IATA** AEROSOLS, flammable**Dangerous Goods Class****ADG Class:** 2.1**Packing Group:** None**Marine pollutant:** No**EMS Number:** F-D,S-U**Hazchem Code:** None**Excepted quantities (EQ):** E0**Limited Quantities:** 1L

## 15 Regulatory Information

**Australian Inventory of Industrial Chemicals:**

All components are on the inventory, or in compliance with the inventory.

(Contd. on page 8)

# Safety Data Sheet

according to WHS Regulations

Print date: 27.03.2023

Revision date: 27.03.2023

**Product Name: 72-847A Trim Tex Adhesive**

(Contd. of page 7)

**Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Poison Schedule:**  
Not a scheduled poison.

## 16 Other Information

**Date of Preparation or Last Revision:** 27.03.2023**Prepared by:** MSDS.COM.AU Pty Ltd

www.msds.com.au

**Abbreviations and acronyms:**

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Press. Gas L: Gases under pressure – Liquefied gas

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity (Oral) 3: Acute toxicity – Category 3

Skin Corrosion/Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Skin Sensitisation 1: Skin sensitisation, Hazard Category 1

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term (Chronic). Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term (Chronic). Category 2

**Disclaimer**

This SDS is prepared in accord with the Safe Work Australia document “Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - July 2020”.

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Wallboard Tool Co. Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.