



Safety Data Sheet

according to WHS & OHS Regulations

Page 1 of 8

Print date: 06.01.2026

Revision date: 23.12.2025

1 Identification

Product Name: Trim-Tex 847au Spray Adhesive

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Adhesive

Details of Manufacturer or Importer:

Wallboard Tool Co. Pty Ltd
30 Leda Drive
Burleigh QLD 4220

Phone Number: 07 5535 7655 / 1300 653 177

Emergency telephone number: National Poisons Information Centre: 13 11 26

2 Hazard(s) Identification

Hazardous Nature:

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition).

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.



GHS02 Flame

Aerosols – Category 1

H222-H229 Extremely flammable aerosol.
Pressurized container: may burst if heated.



GHS08 Health hazard

Specific target organ toxicity (single exposure) – Category 2

H371 May cause damage to the central nervous system and the visual organs.

Specific target organ toxicity (repeated exposure) – Category 1

H372 Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard – Category 1

H304 May be fatal if swallowed and enters airways.



GHS09 Environment

Aquatic Chronic 2

H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin corrosion/irritation – Category 2

H315 Causes skin irritation.

Eye damage/irritation – Category 2A

H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) – Category 3

H336 May cause drowsiness or dizziness.

Signal Word Danger

(Contd. on page 2)

Safety Data Sheet

according to WHS & OHS Regulations

Print date: 06.01.2026

Revision date: 23.12.2025

Product Name: Trim-Tex 847au Spray Adhesive

(Contd. of page 1)

Hazard Statements

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H371 May cause damage to the central nervous system and the visual organs.
 H336 May cause drowsiness or dizziness.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P321 Specific treatment (see on this label).
 P331 Do NOT induce vomiting.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P314 Get medical advice/attention if you feel unwell.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P391 Collect spillage.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition and Information on Ingredients**Chemical Characterization: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Hazardous Components:**

CAS: 67-64-1	Acetone ⚠ Flammable liquids – Category 2, H225; ⚠ Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H336	10-30%
CAS: 79-20-9	Acetic acid, methyl ester ⚠ Flammable liquids – Category 2, H225; ⚠ Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H336	7-13%

(Contd. on page 3)

Safety Data Sheet

according to WHS & OHS Regulations

Print date: 06.01.2026

Revision date: 23.12.2025

Product Name: Trim-Tex 847au Spray Adhesive

(Contd. of page 2)

CAS: 115-10-6	Dimethyl ether ❖ Flammable gases – Category 1A, H220; ❖ Gases under pressure – Compressed gas, H280	5-10%
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light ❖ Specific target organ toxicity (repeated exposure) – Category 1, H372; Aspiration hazard – Category 1, H304; ❖ Skin corrosion/irritation – Category 2, H315; Eye damage/irritation – Category 2A, H319	5-10%
CAS: 142-82-5	Heptane ❖ Flammable liquids – Category 2, H225; ❖ Aspiration hazard – Category 1, H304; ❖ Aquatic Chronic 1, H410; ❖ Skin corrosion/irritation – Category 2, H315; Specific target organ toxicity (single exposure) – Category 3, H336	1-5%
CAS: 67-56-1	Methanol ❖ Flammable liquids – Category 2, H225; ❖ Acute toxicity - oral – Category 3, H301; Acute toxicity - dermal – Category 3, H311; Acute toxicity - inhalation – Category 3, H331; ❖ Specific target organ toxicity (single exposure) – Category 1, H370	0.1-1%

Non Hazardous Components:

Non-hazardous ingredients

4 First Aid Measures**Inhalation:**

If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, wash affected areas with plenty water. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention if irritation persists.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure:

Inhalation: May cause respiratory irritation.

Skin Contact: May cause skin irritation.

Eye Contact: May cause eye irritation.

Ingestion: May cause gastrointestinal irritation, nausea, diarrhoea and vomiting.

5 Fire Fighting Measures**Suitable Extinguishing Media:**

Use fire extinguishing methods suitable to surrounding conditions.

Do not use water jet.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxide of carbon.

Product is Extremely flammable aerosol. Vapors are heavier than air and may travel long distance to source of ignition and flash back.

Closed containers may explode when exposed to extreme heat.

Containers close to fire should be removed only if safe to do so. Use water spray to cool fire exposed containers.

Prevent run-off from fire fighting entering drains or water courses.

(Contd. on page 4)

Safety Data Sheet

according to WHS & OHS Regulations

Print date: 06.01.2026

Revision date: 23.12.2025

Product Name: Trim-Tex 847au Spray Adhesive

(Contd. of page 3)

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection, chemical resistant gloves, protective clothing and safety boots. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb or contain spill with inert material (sand, vermiculite or other appropriate material). Sweep or shovel the spilled material and place into a suitable container for disposal. Use only non-sparking tools. Do not flush into surface water or sewer system.

7 Handling and Storage

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.

Take precautionary measures against static discharge. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Do not expose to temperatures exceeding 50 °C. Keep in fireproof place. Keep away from direct sunlight or other heat sources.

8 Exposure Controls and Personal Protection

Exposure Standards:**CAS: 67-64-1 Acetone**

WES	STEL: 2375 mg/m ³ , 1000 ppm
	TWA: 1185 mg/m ³ , 500 ppm

CAS: 79-20-9 Acetic acid, methyl ester

WES	STEL: 757 mg/m ³ , 250 ppm
	TWA: 606 mg/m ³ , 200 ppm

CAS: 115-10-6 Dimethyl ether

WES	STEL: 950 mg/m ³ , 500 ppm
	TWA: 760 mg/m ³ , 400 ppm

CAS: 142-82-5 Heptane

WES	STEL: 2050 mg/m ³ , 500 ppm
	TWA: 1640 mg/m ³ , 400 ppm

CAS: 67-56-1 Methanol

WES	STEL: 328 mg/m ³ , 250 ppm
	TWA: 262 mg/m ³ , 200 ppm
	Sk

Engineering Controls:**Respiratory Protection:**

Wear an approved respirator if ventilation is insufficient. See Australian Standards AS/NZS 1715 and 1716 for more information.

(Contd. on page 5)

Safety Data Sheet

according to WHS & OHS Regulations

Print date: 06.01.2026

Revision date: 23.12.2025

Product Name: Trim-Tex 847au Spray Adhesive

(Contd. of page 4)

Skin Protection:

Wear protective gloves and protective clothing. See Australian Standards AS/NZS 2161, 2210.1 and 2210.2 for more information.

Eye and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337.

9 Physical and Chemical Properties

Appearance:	Spray aerosol
Form:	Liquid
Colour:	Red
Odour:	Solvent odor
Odour Threshold:	No information available
pH-Value:	7
Melting point/freezing point:	No information available
Initial Boiling Point/Boiling Range:	No information available
Flash Point:	Not applicable
Flammability	Not applicable
Auto-ignition Temperature:	No information available
Decomposition Temperature:	No information available
Explosion Limits:	
Lower:	1 Vol %
Upper:	18 Vol %
Vapour Pressure at 20 °C:	4,136.9-5,515.8 hPa
Relative Density:	0.768
Vapour Density:	No information available
Evaporation Rate:	No information available
Solubility in Water:	Soluble
Partition Coefficient (n-octanol/water):	No information available
Viscosity:	<14 mm ² /s (Kinematic)

10 Stability and Reactivity

Possibility of Hazardous Reactions: No dangerous reactions known under conditions of normal use.

Chemical Stability: Stable at ambient temperature and under normal conditions of storage and use.

Conditions to Avoid: No further relevant information available.

Incompatible Materials: Strong oxidising agents.

Hazardous Decomposition Products: Oxides of carbon.

11 Toxicological Information

Toxicity:**LD50/LC50 Values:****CAS: 67-64-1 Acetone**

Oral	LD50	5,800 mg/kg (Rattus norvegicus (rat))
	LD50	>7,426 mg/kg (Oryctolagus cuniculus (rabbit))
Inhalation	LC50/4 h	30,000 ppm (Rattus norvegicus (rat))

CAS: 79-20-9 Acetic acid, methyl ester

Oral	LD50	6,482 mg/kg (Rattus norvegicus (rat))
		3,705 mg/kg (Oryctolagus cuniculus (rabbit))

(Contd. on page 6)

Safety Data Sheet

according to WHS & OHS Regulations

Print date: 06.01.2026

Revision date: 23.12.2025

Product Name: Trim-Tex 847au Spray Adhesive

(Contd. of page 5)

CAS: 115-10-6 Dimethyl ether		
Inhalation	LC50/4 h	308 mg/l (Rattus norvegicus (rat))
CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light		
Oral	LD50	4,820 mg/kg (Rattus norvegicus (rat))
	LD50	>1,900 mg/kg (Oryctolagus cuniculus (rabbit))
Inhalation	LC50/4 h	>4.96 mg/l (Rattus norvegicus (rat))
CAS: 142-82-5 Heptane		
Oral	LD50	>15,000 mg/kg (Rattus norvegicus (rat))
	LD50	>2,000 mg/kg (Oryctolagus cuniculus (rabbit))
Inhalation	LC50/4 h	103,000 mg/m ³ (Rattus norvegicus (rat))
CAS: 67-56-1 Methanol		
Oral	LD50	1,187 mg/kg (Rattus norvegicus (rat))
Dermal	LD50	17,100 mg/kg (Rattus norvegicus (rat))
Inhalation	LC50/4 h	83.8 mg/l (Rattus norvegicus (rat))

Acute Health Effects**Inhalation:** May cause respiratory irritation.**Skin:** Causes skin irritation.**Eye:** Causes serious eye irritation.**Ingestion:** May cause gastrointestinal irritation, nausea, diarrhoea and vomiting.**Skin Corrosion / Irritation:** Causes skin irritation.**Serious Eye Damage / Irritation:** Causes serious eye irritation.**Respiratory or Skin Sensitisation:** Based on classification principles, the classification criteria are not met.**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:** Based on classification principles, the classification criteria are not met.**Reproductive Toxicity:** Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:**

May cause drowsiness and dizziness.

May cause damage to organs.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard: May be fatal if swallowed and enters airways.**Chronic Health Effects:** No data associated with long term health effects.**Existing Conditions Aggravated by Exposure:** No data available.**12 Ecological Information****Ecotoxicity:****Aquatic toxicity:**

Toxic to aquatic life with long lasting effects.

CAS: 67-64-1 Acetone

EC50/48 h 12,600 mg/l (Daphnia magna (water flea))

LC50/96 h 4,740-6,330 mg/l (Oncorhynchus mykiss (rainbow trout))

CAS: 79-20-9 Acetic acid, methyl ester

EC50/48 h 1,026.7 mg/l (Daphnia magna (water flea))

LC50/96 h 295-348 mg/l (Pimephales promelas (fathead minnow))

(Contd. on page 7)

Safety Data Sheet

according to WHS & OHS Regulations

Print date: 06.01.2026

Revision date: 23.12.2025

Product Name: Trim-Tex 847au Spray Adhesive

(Contd. of page 6)

CAS: 115-10-6 Dimethyl ether	
EC50/48 h	4.3-7.8 mg/l (Daphnia magna (water flea))
LC50/96 h	10,302-16,743 mg/l (fish)
CAS: 142-82-5 Heptane	
EC50/24 h	>10 mg/l (Daphnia magna (water flea))
LC50/96 h	375 mg/l (fish)
CAS: 67-56-1 Methanol	
LC50/96 h	13,500-17,600 ppm (Lepomis macrochirus (bluegill))
	19,500-20,700 ppm (Oncorhynchus mykiss (rainbow trout))
LC50/96 h	28,200 mg/l (Pimephales promelas (fathead minnow))

Persistence and Degradability: No data available on finished product.**Bioaccumulative Potential:** No data available on finished product.**Mobility in Soil:** No data available on finished product.**Other adverse effects:** No further relevant information available.**13 Disposal Considerations****Disposal Methods and Containers:** Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

14 Transport Information**UN Number**

ADG, IMDG, IATA

UN1950

Proper Shipping Name

ADG

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable

Dangerous Goods Class

ADG Class:

2.1

Packing Group:

ADG, IMDG, IATA

-

EMS Number:

F-D,S-U

Special Provisions:

63, 190, 277, 327, 344, 381

Excepted quantities (EQ):

E0

Limited Quantities:

1L

Packagings & IBCs - Packing Instruction:

P207, LP200

Packagings & IBCs - Special Packing Provisions:

PP87, L2

15 Regulatory Information**Australian Inventory of Industrial Chemicals:**

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Poison Schedule:

Not a scheduled poison.

(Contd. on page 8)

Safety Data Sheet

according to WHS & OHS Regulations

Print date: 06.01.2026

Revision date: 23.12.2025

Product Name: Trim-Tex 847au Spray Adhesive

(Contd. of page 7)

16 Other Information**Date of Preparation or Last Revision:** 23.12.2025**Prepared by:** MSDS.COM.AU Pty Ltdwww.msds.com.au**Abbreviations and acronyms:**

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Flammable gases – Category 1A: Flammable gases – Category 1A

Aerosols – Category 1: Aerosols – Category 1

Gases under pressure – Compressed gas: Gases under pressure – Compressed gas

Flammable liquids – Category 2: Flammable liquids – Category 2

Acute toxicity - oral – Category 3: Acute toxicity – Category 3

Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2

Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

Specific target organ toxicity (single exposure) – Category 1: Specific target organ toxicity (single exposure) – Category 1

Specific target organ toxicity (single exposure) – Category 2: Specific target organ toxicity (single exposure) – Category 2

Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3

Specific target organ toxicity (repeated exposure) – Category 1: Specific target organ toxicity (repeated exposure) – Category 1

Aspiration hazard – Category 1: Aspiration hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term (Chronic). Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term (Chronic). Category 2

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - June 2023".

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Wallboard Tool Co Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.